



Transform your project with Suberlev from Falconstema, an innovation in thermal and acoustic insulation.

FUNGILEV SANITARY CLEANER



Technical sheet

DESCRIPTION

Disinfectant product in a wide-spectrum aqueous solution. Action against bacteria, Yeasts, moulds and algae.

APPLICATION

Recommended for

- Disinfection of surfaces contaminated by all types of micro-organisms, including fungi and algae.
- Protect against the growth of microorganisms.
- Treat preventively before applying paint or sprayed cork.
- Encapsulate the asbestos before applying the sprayed cork.

SURFACES

- Concrete, cement, plaster, BA13, wood, painted surfaces, fiber cement, wood, galvanized steel, mortar, ceramic brick, etc.

INSTRUCTIONS

- To **protect surfaces** from possible **infections**:
 - The surface must be free of dirt.
 - Once cleaned, it is applied directly to the surface with roller, brush or spray. It is advisable to apply two crossed layers.
- To **disinfect** and **clean surfaces**:
 - You must clean the surface dirt of microorganisms, with soapy water or bleach.
 - Once clean apply the product with roller, brush or spray. It is advisable to apply two crossed layers.

RECOMMENDED CONSUMPTION

- **6 - 8 m²/L** (approx. 0,15 L/m²)

RECOMMENDATION OF USE

- Application temperature 5 - 35 °C.
- Repaint after 3 - 4 hours of drying.

SALES FORMAT

- **1 L** bottles
- **5 L** Bottles

STORAGE

- **Store** in a **cool place**, at a temperature between **5 - 45°C**, away from exposure to sunlight and frost. **Up to 2 years** from the date of manufacture, in the original container sealed and protected from moisture. One open use **within 15 days**.

SPECIFICATIONS / TECHNICAL DATA SHEET

- **Appearance and Colour:** Slightly yellowish transparent liquid
- **Odour:** Characteristic
- **Density:** 1 ± 0.05 kg/L
- **pH:** 3.0 - 5.0
- **Solubility:** Fully soluble in water

PRECAUTION

- Keep out of reach of children.
- Prevent the product from meeting skin and eyes.
- Avoid inhaling steam, apply it in a well-ventilated place.
- Use personal protection such as glasses, masks, etc.
- No discharge into sewers is permitted.

NOTE

SUBERLEV products must be applied by applicators approved by the manufacturer.

The above information is based on our practical experience and laboratory tests. Given the wide variety of construction materials available and the many application methods beyond our control. It is essential to carry out sufficient practical tests and verifications in each case to ensure the compatibility of the product with each specific application.

